

Screen Printing with Screen Filler and Drawing Fluid Additional Information

FEATURED PRODUCTS

- [Cream Opalescent \(000420-0030-F\)](#)
- [White Opalescent sheet \(000113-0030-F\)](#)
- [Driftwood Gray Opalescent \(000132-0030-F\)](#)
- [Tangerine Orange Opalescent \(000025-0030-F\)](#)
- [Sunflower Yellow Opalescent \(000220-0030-F\)](#)
- [Petal Pink Opalescent \(000421-0030-F\)](#)
- [Bullseye Shelf Primer \(8220\) \(8222\)](#)
- [Disposable Particulate Respirator N100 \(8261\)](#)
- [Spartan Glass Cleaner Concentrate \(8236\)](#)
- [Toyo Self-Oiling Cutter \(7010\)](#)

HARDWARE/ART SUPPLIES

- Brushes
- Bucket
- Comet®
- Masking tape
- Palette knife
- Pencil
- Pressure washer
- Screen stain remover
- Soft Scrub®
- Sponge

SCREEN PRINTING SUPPLIES

- [Emulsion Scoop Coater \(7052\)](#)
- [High-temperature enamels \(reuscheco.com\)](#)
- Power Washer (hardware or big box store)
- [Printing Screen, 230-mesh \(7051\)](#)
- [Screen Printing Hinge Clamps \(7063\)](#)
- [Screen Printing Medium \(reuscheco.com\)](#)
- [Screen Printing Squeegee \(7061\)](#)
- [Screen Spray-out Nozzle \(7053\)](#)
- [Scrub Pad, Blue, Firm \(7043\)](#)
- [Speedball Drawing Fluid \(7067\)](#)
- [Speedball Screen Filler \(7066\)](#)

TACK FUSING SCHEDULE

| RATE | TEMPERATURE | HOLD |
|---------------|----------------|------|
| 400°F (222°C) | 1350°F (704°C) | :10 |
| AFAP | 900°F (482°C) | :45 |
| 100°F (56°C) | 700°F (371°C) | :00 |
| AFAP | 70°F (21°C) | :00 |